

## SAFETY DATA SHEET

## Kontaktlim 281

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

## 1.1. Product identifier

## Trade name

Kontaktlim 281

## ▼ Product no.

281

## ▼ Unique formula identifier (UFI)

WRP0-F0VK-X002-6W8Q

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

## Relevant identified uses of the substance or mixture

Contact gluing

## Use descriptors (REACH)

Sectors of use	Description
LCS "C"	Consumer uses: Private households (= general public = consumers)
LCS "PW"	Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Product category	Description
PC 1	Adhesives, Sealants
Process category	Description
PROC 10	Roller application or brushing
Environmental release category	Description
ERC 8a	Wide dispersive indoor use of processing aids in open systems
ERC 8d	Wide dispersive outdoor use of processing aids in open systems

## Uses advised against

None known.

## 1.3. Details of the supplier of the safety data sheet

## Company and address

**Dana Lim A/S**

Københavnsvej 220

DK-4600 Køge

Denmark

Tel: +45 56 64 00 70

## Contact person

Product Safety Department

## E-mail

info@danalim.dk

## Revision

09/08/2024

## SDS Version

5.0

## Date of previous version

29/05/2024 (4.0)

## 1.4. Emergency telephone number

Contact the poison hotline: +45 82 12 12 12 (24 hour service)

See section 4 "First aid measures".

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.  
 Skin Irrit. 2; H315, Causes skin irritation.  
 Eye Irrit. 2; H319, Causes serious eye irritation.  
 STOT SE 3; H335, May cause respiratory irritation.  
 STOT SE 3; H336, May cause drowsiness or dizziness.  
 STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.  
 Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

### 2.2. Label elements

#### Hazard pictogram(s)



#### Signal word

Danger

#### Hazard statement(s)

Highly flammable liquid and vapour. (H225)  
 Causes skin irritation. (H315)  
 Causes serious eye irritation. (H319)  
 May cause respiratory irritation. (H335)  
 May cause drowsiness or dizziness. (H336)  
 May cause damage to organs through prolonged or repeated exposure. (H373)  
 Toxic to aquatic life with long lasting effects. (H411)

#### Precautionary statement(s)

##### General

If medical advice is needed, have product container or label at hand. (P101)  
 Keep out of reach of children. (P102)

##### ▼ Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)  
 Use only outdoors or in a well-ventilated area. (P271)

##### ▼ Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
 Continue rinsing. (P305+P351+P338)

##### Storage

Store in a well-ventilated place. Keep cool. (P403+P235)

##### ▼ Disposal

-

##### ▼ Hazardous substances

reaction mass of ethylbenzene and xylene  
 ethyl acetate  
 Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic

#### Additional labelling

EUH208, Contains Colophony, disulfiram. May produce an allergic reaction.

UFI: WRP0-F0VK-X002-6W8Q

### 2.3. Other hazards

#### Additional warnings

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.  
 This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Not applicable. This product is a mixture.

### 3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
reaction mass of ethylbenzene and xylene	CAS No.: EC No.: 905-588-0 REACH: 01-2119488216-32-xxxx, 01-2119486136-34-xxxx Index No.:	25-40%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Acute Tox. 4, H332 STOT SE 3, H335 STOT RE 2, H373	[1]
ethyl acetate	CAS No.: 141-78-6 EC No.: 205-500-4 REACH: 01-2119475103-46-XXXX Index No.: 607-022-00-5	25-40%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic	CAS No.: EC No.: 927-510-4 REACH: 01-2119475515-33-xxxx Index No.:	15-25%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	
zinc oxide	CAS No.: 1314-13-2 EC No.: 215-222-5 REACH: 01-2119463881-32-XXXX Index No.: 030-013-00-7	<1%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
Colophony	CAS No.: 8050-09-7 EC No.: 232-475-7 REACH: 01-2119480418-32-0000 Index No.: 650-015-00-7	<1%	Skin Sens. 1, H317	
cyclohexane	CAS No.: 110-82-7 EC No.: 203-806-2 REACH: 01-2119463273-41-XXXX Index No.: 601-017-00-1	<1%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1], [3]
2,6-di-tert-butyl-p-cresol	CAS No.: 128-37-0 EC No.: 204-881-4 REACH: Index No.:	<1%	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
xylene	CAS No.: 1330-20-7 EC No.: 215-535-7 REACH: 01-2119488216-32-XXXX Index No.: 601-022-00-9	<1%	Flam. Liq. 3, H226 Acute Tox. 4, H312 Skin Irrit. 2, H315 Acute Tox. 4, H332	[1]
disulfiram	CAS No.: 97-77-8 EC No.: 202-607-8 REACH: 01-2119555278-30-XXXX Index No.: 006-079-00-8	<0,3%	Acute Tox. 4, H302 Skin Sens. 1, H317 STOT RE 2, H373 Aquatic Acute 1, H400 (M=10) Aquatic Chronic 1, H410 (M=10)	
benzene	CAS No.: 71-43-2 EC No.: 200-753-7 REACH: 01-2119447106-44-XXXX Index No.: 601-020-00-8	<0.05%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Irrit. 2, H319 Muta. 1B, H340 Carc. 1A, H350	[1], [3], [4]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

#### Other information

[1] European occupational exposure limit.

[3] According to REACH, Annex XVII, the substance is subject to restrictions.

[4] Substance is listed in Annex I of the Prior Informed Consent Regulation (PIC, Regulation (EU) 649/2012).

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

##### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

##### Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners. If skin irritation occurs: Get medical advice/attention.

##### Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

##### Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

##### Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Sensitisation: This product contains substances, which may trigger allergic reaction upon dermal contact.

Manifestation of allergic reactions typically takes place within 12-72 hours after exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

##### Information to medics

Bring this safety data sheet or the label from this product.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Highly flammable liquid and vapour.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and

nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the chemical emergency services on 72 85 20 00 (24 h service) in order to obtain further advice.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Ensure adequate ventilation, especially in confined areas.

Avoid inhalation of vapours from spilled material.

Contaminated areas may be slippery.

### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

### 6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

It is recommended to install waste collection trays in order to prevent emissions to the waste water system and surrounding environment.

Avoid direct contact with the product.

Avoid contact during pregnancy and while nursing.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

#### Recommended storage material

Always store in containers of the same material as the original container.

#### Fire class

In accordance with the statutory order on flammable liquids the product is classified as a liquid of class I, subclass 1 (1 storage unit = 1 liter).

#### Storage conditions

Dry, cool and well ventilated

#### Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

reaction mass of ethylbenzene and xylene  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 109  
Long term exposure limit (8 hours) (ppm): 25  
Annotations:  
E = Substance has an EC limit.  
H = The substance can be absorbed through the skin.

ethyl acetate  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 540  
Long term exposure limit (8 hours) (ppm): 150  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1468  
Short term exposure limit (15 minutes) (ppm): 400  
Annotations:  
E = Substance has an EC limit.

zinc oxide  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 4 (som Zn)  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 8 (som Zn)

cyclohexane  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 172  
Long term exposure limit (8 hours) (ppm): 50  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 344  
Short term exposure limit (15 minutes) (ppm): 100  
Annotations:  
E = Substance has an EC limit.

2,6-di-tert-butyl-p-cresol  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 10  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 20

xylene  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 109  
Long term exposure limit (8 hours) (ppm): 25  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 442  
Short term exposure limit (15 minutes) (ppm): 100  
Annotations:  
E = Substance has an EC limit.  
H = The substance can be absorbed through the skin.

disulfiram  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 2  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 4

benzene  
Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1,6  
Long term exposure limit (8 hours) (ppm): 0,5  
Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 3.2  
Short term exposure limit (15 minutes) (ppm): 1  
Annotations:  
E = Substance has an EC limit.  
H = The substance can be absorbed through the skin.  
K = The substance may cause cancer.

Statutory order 291 on exposure limits for substances and mixtures (19/03/2024)

benzene is included in the national list of substances suspected of causing cancer

BEK no. 290 of 19/03/2024 on measures to prevent the risk when working with carcinogenic, mutagenic or reproductively toxic substances and materials.

## DNEL

### 2,6-di-tert-butyl-p-cresol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	5 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	8,3 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	1,74 mg/m <sup>3</sup>
Long term – Systemic effects - Workers	Inhalation	5,8 mg/m <sup>3</sup>

### ethyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - Workers	Dermal	63 mg/kg bw/day

## PNEC

### 2,6-di-tert-butyl-p-cresol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,004 mg/L
Intermittent release		0,004 mg/L
Marine water		0,0004 mg/L
Sewage treatment plant		100 mg/L
Soil		1,04 mg/kg

### xylene

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		327 µg/L
Freshwater sediment		12.46 mg/kg sediment dw
Marine water		327 µg/L
Marine water sediment		12.46 mg/kg sediment dw
Sewage treatment plant		6.58 mg/L

## 8.2. ▼ Exposure controls

Apply general control to prevent unnecessary exposure

### General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

### Exposure scenarios

Indoor use of:

Product packaged in tubes on small adhesive surfaces: ensure good ventilation, e.g. open window (air change 3-5 times an hour)

Product packaged in cans on larger adhesive surfaces: use local exhaust ventilation (air change 10-15 times an hour)

The product's packaging must be closed with a lid when not in use.

### ▼ Exposure limits

Occupational exposure limits have not been defined for the substances in this product.

### ▼ Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of vapours.

### Hygiene measures

Take off contaminated clothing and wash it before reuse.

### Measures to avoid environmental exposure

Keep damming materials near the workplace. If possible, collect spillage during work.

## Individual protection measures, such as personal protective equipment

### Generally

In the event the work process is within scope of the Danish statutory order on work with code numbered products (Work Inspectorate Order no. 302/1993), then personal protection equipment shall be selected as set out herein. If applicable, please refer to the code number of this product in section 15.

Use only CE marked protective equipment.

### Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of insufficient ventilation	A	Class 2 (medium capacity)	Brown	EN14387



### Skin protection

Recommended	Type/Category	Standards
Dedicated work clothing should be worn. Wear a protective suit in the event of prolonged periods of work with the product.	-	-



### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0.5	> 30	EN374-2, EN374-3, EN388



### Eye protection

Type	Standards
Wear safety glasses with side shields.	EN166



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Liquid

#### Colour

Yellow

#### Odour / Odour threshold

Testing not relevant or not possible due to the nature of the product.

#### pH

Testing not relevant or not possible due to the nature of the product.

#### Density (g/cm<sup>3</sup>)

0.87

#### Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

#### Particle characteristics

Does not apply to liquids.

#### Phase changes

##### Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

##### Softening point/range (°C)

Does not apply to liquids.

##### Boiling point (°C)

104

##### Vapour pressure

Testing not relevant or not possible due to the nature of the product.

##### Relative vapour density

Testing not relevant or not possible due to the nature of the product.

##### Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

#### Data on fire and explosion hazards

Flash point (°C)

7

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

#### Solubility

Solubility in water

Insoluble

n-octanol/water coefficient (LogKow)

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

#### 9.2. Other information

Other physical and chemical parameters

No data available.

Oxidizing properties

Testing not relevant or not possible due to the nature of the product.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No data available.

#### 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

#### 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

#### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

#### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

Product/substance	ethyl acetate
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	5600 mg/kg ·

Product/substance	ethyl acetate
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	56000 mg/l/4h ·

Product/substance	zinc oxide
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50

Result: 2500 mg/min ·

Product/substance zinc oxide  
 Species: Rat  
 Route of exposure: Oral  
 Test: LD50  
 Result: 7950 mg/kg ·

Product/substance cyclohexane  
 Species: Rat  
 Route of exposure: Oral  
 Test: LD50  
 Result: 5000 mg/kg ·

Product/substance xylene  
 Species: Rat  
 Route of exposure: Oral  
 Test: LD50  
 Result: >3900 mg/kg ·

Product/substance xylene  
 Species: Rat  
 Route of exposure: Inhalation  
 Test: LC50  
 Result: 20 mg/l 4h ·

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/irritation

Causes serious eye irritation.

#### Respiratory sensitisation

Based on available data, the classification criteria are not met.

#### Skin sensitisation

This product contains substances that may trigger an allergic reaction in already sensitized persons.

#### Germ cell mutagenicity

Based on available data, the classification criteria are not met.

#### Carcinogenicity

Based on available data, the classification criteria are not met.

#### Reproductive toxicity

Based on available data, the classification criteria are not met.

#### STOT-single exposure

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

#### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

#### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

#### Other information

reaction mass of ethylbenzene and xylene has been classified by IARC as a group 3 carcinogen.

2,6-di-tert-butyl-p-cresol has been classified by IARC as a group 3 carcinogen.

xylene has been classified by IARC as a group 3 carcinogen.  
 disulfiram has been classified by IARC as a group 3 carcinogen.  
 benzene has been classified by IARC as a group 1 carcinogen.

## SECTION 12: Ecological information

### 12.1. ▼ Toxicity

Product/substance ethyl acetate  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: >200 mg/l ·

Product/substance ethyl acetate  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: >700 mg/l ·

Product/substance ethyl acetate  
 Species: Algae  
 Duration: 72 hours  
 Test: IC50  
 Result: >100 mg/l ·

Product/substance ethyl acetate  
 Species: Daphnia, Daphnia magna  
 Duration: 24 hours  
 Test: EC50  
 Result: 2500-3090 mg/L

Product/substance ethyl acetate  
 Species: Daphnia, Daphnia magna  
 Duration: 21 days  
 Test: NOEC  
 Result: 2,4 mg/L

Product/substance zinc oxide  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: >1000 mg/l ·

Product/substance zinc oxide  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: 1,1 mg/l ·

Product/substance zinc oxide  
 Species: Algae  
 Duration: 72 hours  
 Test: EC50  
 Result: 0,17 mg/l ·

Product/substance cyclohexane  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: 0,9 mg/l ·

Product/substance 2,6-di-tert-butyl-p-cresol  
 Species: Fish, Danio rerio

Duration: 96 hours  
 Test: LCLo  
 Result: > 0,57 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol  
 Species: Daphnia, Daphnia magna  
 Duration: 48 hours  
 Test: LC50  
 Result: 0,61 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol  
 Species: Algae, Desmodesmus subspicatus  
 Duration: 72 hours  
 Test: IC50  
 Result: > 0,4 mg/L

Product/substance 2,6-di-tert-butyl-p-cresol  
 Species: Bacteria  
 Duration: 3 hours  
 Test: EC50  
 Result: > 10000 mg/L

Product/substance xylene  
 Species: Fish  
 Duration: 96 hours  
 Test: LC50  
 Result: 2 mg/l ·

Product/substance xylene  
 Species: Daphnia  
 Duration: 48 hours  
 Test: EC50  
 Result: 8,5 mg/l ·

Product/substance xylene  
 Species: Algae  
 Duration: 72 hours  
 Test: LC50  
 Result: 3,2 mg/l ·

Toxic to aquatic life with long lasting effects.

#### 12.2. Persistence and degradability

Product/substance ethyl acetate  
 Conclusion: Readily biodegradable

Product/substance 2,6-di-tert-butyl-p-cresol  
 Duration: 28 days  
 Result: 4,5 %  
 Conclusion: Not biodegradable  
 Test: OECD 301 C

Product/substance xylene  
 Conclusion: Readily biodegradable

#### 12.3. Bioaccumulative potential

Product/substance xylene  
 BCF: 24  
 LogKow: 3,1500  
 Conclusion: -

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

#### 12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste. (\*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 6 - Acute toxicity

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

#### EWC code

08 04 09\*

Waste adhesives and sealants containing organic solvents or other dangerous substances

#### Specific labelling

Not applicable.

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1  	II	Yes	Limited quantities: 5 L EmS: F-E S-D See below for additional information.
IATA	UN1133	ADHESIVES	Transport hazard class: 3 Label: 3 Classification code: F1 	II	Yes	See below for additional information.

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
					

\* Packing group

\*\* Environmental hazards

#### Additional information

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

#### 14.6. Special precautions for user

Not applicable.

#### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

#### ▼ REACH, Annex XVII

cyclohexane is subject to REACH restrictions (entry 57).

benzene is subject to REACH restrictions (entry 05).

reaction mass of ethylbenzene and xylene is subject to REACH restrictions (entry 40).

ethyl acetate is subject to REACH restrictions (entry 40).

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclic is subject to REACH restrictions (entry 40).

cyclohexane is subject to REACH restrictions (entry 40).

xylene is subject to REACH restrictions (entry 40).

benzene is subject to REACH restrictions (entry 40).

#### Product registration number

151651

#### Regulation on work involving coded products

Code number (1993): 3-6

#### Additional information

Tactile warning.

#### Sources

The Danish Working Environment Authority's executive order no. 1049 of 30 May 2021 on young people's work.

Based on Council Directive 94/33 / EC of 22 June 1994 on the protection of young people at work.

Pregnant workers and workers who are breastfeeding (AT Guide A.1.8-6, amended 2020).

Executive Order no. 372 of 25 April 2016 on control of the risk of major accidents with dangerous substances.

Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals (with subsequent amendments).

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Arbejdstilsynets bekendtgørelse nr. 301 af 13. maj 1993 om fastsættelse af kodenumre med senere ændringer.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

No

### SECTION 16: Other information

#### Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.  
H225, Highly flammable liquid and vapour.  
H226, Flammable liquid and vapour.  
H302, Harmful if swallowed.  
H304, May be fatal if swallowed and enters airways.  
H312, Harmful in contact with skin.  
H315, Causes skin irritation.  
H317, May cause an allergic skin reaction.  
H319, Causes serious eye irritation.  
H332, Harmful if inhaled.  
H335, May cause respiratory irritation.  
H336, May cause drowsiness or dizziness.  
H340, May cause genetic defects.  
H350, May cause cancer.  
H372, Causes damage to organs through prolonged or repeated exposure.  
H373, May cause damage to organs through prolonged or repeated exposure.  
H400, Very toxic to aquatic life.  
H410, Very toxic to aquatic life with long lasting effects.  
H411, Toxic to aquatic life with long lasting effects.

#### The full text of identified uses as mentioned in section 1

LCS "C" = Consumer uses: Private households (= general public = consumers)  
LCS "PW" = Professional uses: Public domain (administration, education, entertainment, services, craftsmen)  
PROC 10 = Roller application or brushing  
PC 1 = Adhesives, Sealants  
ERC 8a = Wide dispersive indoor use of processing aids in open systems  
ERC 8d = Wide dispersive outdoor use of processing aids in open systems

#### Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway  
ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road  
ATE = Acute Toxicity Estimate  
BCF = Bioconcentration Factor  
CAS = Chemical Abstracts Service  
CE = Conformité Européenne (European conformity)  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
CSA = Chemical Safety Assessment  
CSR = Chemical Safety Report  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EINECS = European Inventory of Existing Commercial chemical Substances  
ES = Exposure Scenario  
EUH statement = CLP-specific Hazard statement  
EuPCS = European Product Categorisation System  
EWC = European Waste Catalogue  
GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
GWP = Global warming potential  
IARC = International Agency for Research on Cancer (IARC)  
IATA = International Air Transport Association  
IBC = Intermediate Bulk Container  
IMDG = International Maritime Dangerous Goods  
LogPow = logarithm of the octanol/water partition coefficient  
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
OECD = Organisation for Economic Co-operation and Development  
PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration  
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail  
RRN = REACH Registration Number  
SCL = A specific concentration limit  
SVHC = Substances of Very High Concern  
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure  
STOT-SE = Specific Target Organ Toxicity - Single Exposure  
TWA = Time weighted average  
UN = United Nations  
UVBC = Unknown or variable composition, complex reaction products or of biological materials  
VOC = Volatile Organic Compound  
vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

#### The safety data sheet is validated by

Product Safety Department

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: DK-en